



WEVER & DUCRÉ
LIGHTING

GETTON FLOOR 1.0

717574D4

Project

Type

Notes

Quantity

Date

GENERAL

Floor
Surface
Dark Grey Texture
IP65
Exterior
720 lm

LED



3000 K
CRI 80
L90 / 50000 h
3-step binning
MR 0.54
MDER 0.49

PHYSICAL


Diameter 120 mm
Height 120 mm
0.8 kg

ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 7.6 W
PC1
Safety distance 0.3 m



LIGHT DISTRIBUTION



[717574D4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

GETTON FLOOR 1.0

717574D4

BASE

BASE 275

TYPE	Ø · H (MM)	ORDERCODE
GETTON	∅122 · 275	9 1 0 0 5 2 D 0

BASE 475

TYPE	Ø · H (MM)	ORDERCODE
GETTON	∅122 · 475	9 1 0 0 5 4 D 0

BASE 675

TYPE	Ø · H (MM)	ORDERCODE
GETTON	∅122 · 675	9 1 0 0 5 8 D 0

GROUND SPIKE

Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
GETTON POLE	∅122 · 357	9 0 0 1 3 1 0 1