



MAP  
OUTDOOR  
FLOOR RECESSED



0.6

LED 5W | 220-240VAC | 50-60Hz  
COB 3-step | stainless steel | glass  
1.6m cable | aluminium powder  
coated

0.38kg IP67 IK08 3~0.3~D 16

38° 100

CODE  
751163L

LIGHT COLOUR LUMEN | CRI CODE  
3000K 200 | >80 4

OPTIONAL

CODE  
ground housing 90012201



0.9

LED 8W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

0.70kg IP67 IK08 3~0.3~D 16


38° 135

CODE  
751264L

LIGHT COLOUR LUMEN | CRI CODE  
3000K 470 | >80 4

OPTIONAL

CODE  
ground housing 90012202



1.2

LED 12W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

1.01kg IP67 IK08 3~0.3~D 16


38° 120

CODE  
751364L

LIGHT COLOUR LUMEN | CRI CODE  
3000K 815 | >80 4

OPTIONAL

CODE  
ground housing 90012203



1.6

LED 15W | 220-240VAC | 50-60Hz  
COB 3-step | phase-cut dim  
stainless steel | glass | 1.6m cable  
aluminium powder coated

1.01kg IP67 IK09 3~0.3~D 16

41° 185

CODE  
751464L

LIGHT COLOUR LUMEN | CRI CODE  
3000K 1030 | >80 4

OPTIONAL

CODE  
ground housing 90012204

