



WEVER & DUCRÉ
LIGHTING

STREX MODULE 1.0 OPAL

171385W5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Track

Signal White

1061 lm/m

IP20

Interior

640 lm

RAL 9003^a

LED

3000 K

CRI 90

L70 / 50000 h

3-step binning

PHYSICAL

Length 693 mm

Width 16 mm

Height 18 mm

0.16 kg

693 (adapter) mm

48V System

ELECTRICAL

DALI dim

48 V


Total connected power 12.1 W

PC3


Safety distance 0.3 m

20 W/m


^a RAL Palette colors may deviate slightly due to production conditions.



Linear light inset for 48V tracks; opal PMMA cover; surface Signal White; powder coated; matt texture; RAL 9003; PCB 3-step binning; DALI dim; light colour 3000 K; Binning initial 3 MacAdam; CRI 90; 48 V; degree of protection IP20; PC3; light source not replaceable;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

STREX MODULE 1.0 OPAL

171385W5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.91	0.86	0.82	0.77
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL

Track Profile 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system suspended indirect light	Jet Black	2000-26-29	9 0 0 1 4 0 B 5
STREX system suspended indirect light	Signal White	2000-26-29	9 0 0 1 4 0 W 5
STREX system surface/suspended	Signal White	2000-26-29	9 0 0 1 4 1 8 3
STREX system surface/suspended	Jet Black	2000-26-29	9 0 0 1 4 1 8 4
STREX system recessed	Signal White	2000-37-33	9 0 0 1 4 1 8 9
STREX system recessed	Jet Black	2000-37-33	9 0 0 1 4 1 9 0
STREX system custom cut suspended indirect light	Jet Black	1000-1999-26-29	9 0 0 1 4 0 B 5 C C
STREX system custom cut suspended indirect light	Signal White	1000-1999-26-29	9 0 0 1 4 0 W 5 C C
STREX system custom cut surface/suspended	Signal White	1001-1999-26-29	9 0 0 1 4 1 8 3 C C
STREX system custom cut surface/suspended	Jet Black	1001-1999-26-29	9 0 0 1 4 1 8 4 C C
STREX system custom cut recessed	Signal White	1001-1999-37-33	9 0 0 1 4 1 8 9 C C
STREX system custom cut recessed	Jet Black	1001-1999-37-33	9 0 0 1 4 1 9 0 C C

End Cap

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	Signal White	26-2.5-29	9 0 0 1 4 1 4 7
STREX system surface/suspended	Jet Black	26-2.5-29	9 0 0 1 4 1 4 8
STREX system recessed	Signal White	37-10-27	9 0 0 1 4 1 4 9
STREX system recessed	Jet Black	37-10-27	9 0 0 1 4 1 5 0

Power Feed

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	Signal White	112-18	9 0 0 1 4 1 5 3
STREX system	Jet Black	112-18	9 0 0 1 4 1 5 4



WEVER & DUCRÉ
LIGHTING

STREX MODULE 1.0 OPAL

171385W5

Suspension Set

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system 1.5m suspended	Stainless Steel	80-23-1500	9 0 0 1 4 1 6 0
STREX system 3.0m suspended	Stainless Steel	80-23-3000	9 0 0 1 4 1 6 1
STREX system 1.5m suspended	Jet Black	80-23-1500	9 0 0 1 4 2 7 4
STREX system 3.0m suspended	Jet Black	80-23-3000	9 0 0 1 4 2 7 5

Power Supply 100W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Signal White	439-26-44	9 0 0 1 4 1 6 6
STREX system surface	Jet Black	439-26-44	9 0 0 1 4 1 6 7
STREX system suspended	Signal White	439-26-44	9 0 0 1 4 1 6 8
STREX system suspended	Jet Black	439-26-44	9 0 0 1 4 1 6 9
STREX system suspended	Signal White	439-26-44	9 0 0 1 4 2 6 0
STREX system suspended	Jet Black	439-26-44	9 0 0 1 4 2 6 1
STREX system		350-30-18	9 0 2 1 8 9 0 1

Power Supply 150W

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface	Signal White	439-26-44	9 0 0 1 4 1 7 0
STREX system surface	Jet Black	439-26-44	9 0 0 1 4 1 7 1
STREX system suspended	Signal White	439-26-44	9 0 0 1 4 1 7 2
STREX system suspended	Jet Black	439-26-44	9 0 0 1 4 1 7 3
STREX system suspended	Signal White	439-26-44	9 0 0 1 4 2 6 2
STREX system suspended	Jet Black	439-26-44	9 0 0 1 4 2 6 3
STREX system		350-30-18	9 0 2 1 8 9 0 2

In Track Power Supply 80W

TYPE	L · W · H (MM)	ORDERCODE
STREX system suspended	150-26-44	9 0 0 1 4 1 7 4
STREX system surface	150-26-29	9 0 0 1 4 1 7 6

In Track Power Supply 230W

TYPE	L · W · H (MM)	ORDERCODE
STREX system suspended	150-26-44	9 0 0 1 4 1 7 5
STREX system surface	150-26-29	9 0 0 1 4 1 7 7

Track Profile 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	Signal White	1000-26-29	9 0 0 1 4 1 8 1
STREX system surface/suspended	Jet Black	1000-26-29	9 0 0 1 4 1 8 2
STREX system recessed	Signal White	1000-37-33	9 0 0 1 4 1 8 7
STREX system recessed	Jet Black	1000-37-33	9 0 0 1 4 1 8 8
STREX system custom cut surface/suspended	Signal White	200-999-26-29	9 0 0 1 4 1 8 1 C C
STREX system custom cut surface/suspended	Jet Black	200-999-26-29	9 0 0 1 4 1 8 2 C C
STREX system custom cut recessed	Signal White	200-999-37-33	9 0 0 1 4 1 8 7 C C
STREX system custom cut recessed	Jet Black	200-999-37-33	9 0 0 1 4 1 8 8 C C



WEVER & DUCRÉ
LIGHTING

STREX MODULE 1.0 OPAL

171385W5

Track Profile 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	Signal White	3000-26-29	9 0 0 1 4 1 8 5
STREX system surface/suspended	Jet Black	3000-26-29	9 0 0 1 4 1 8 6
STREX system recessed	Signal White	3000-37-33	9 0 0 1 4 1 9 1
STREX system recessed	Jet Black	3000-37-33	9 0 0 1 4 1 9 2
STREX system suspended indirect light	Jet Black	3000-26-29	9 0 0 1 4 1 B 5
STREX system suspended indirect light	Signal White	3000-26-29	9 0 0 1 4 1 W 5
STREX system custom cut surface/suspended	Signal White	2001-2999-26-29	9 0 0 1 4 1 8 5 C C
STREX system custom cut surface/suspended	Jet Black	2001-2999-26-29	9 0 0 1 4 1 8 6 C C
STREX system custom cut recessed	Signal White	2001-2999-37-33	9 0 0 1 4 1 9 1 C C
STREX system custom cut recessed	Jet Black	2001-2999-37-33	9 0 0 1 4 1 9 2 C C
STREX system custom cut suspended indirect light	Jet Black	2001-2999-26-29	9 0 0 1 4 1 B 5 C C
STREX system custom cut suspended indirect light	Signal White	2001-2999-26-29	9 0 0 1 4 1 W 5 C C

Mounting Bracket

TYPE	ORDERCODE
STREX system recessed	9 0 0 1 4 1 9 3

Wireless Control

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	Signal White	143-58	9 0 0 1 4 1 9 4
STREX system	Jet Black	143-58	9 0 0 1 4 1 9 5

Connector

TYPE	COLOUR	L · H (MM)	ORDERCODE
STREX system	Signal White	105-18	9 0 0 1 4 1 9 6
STREX system	Jet Black	105-18	9 0 0 1 4 1 9 7

L-Connector

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system surface/suspended	Signal White	105-105-18	9 0 0 1 4 1 9 8
STREX system surface/suspended	Jet Black	105-105-18	9 0 0 1 4 1 9 9
STREX system recessed	Signal White	105-105-18	9 0 0 1 4 2 5 1
STREX system recessed	Jet Black	105-105-18	9 0 0 1 4 2 5 2

L-Connector non-electrical

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system recessed	Signal White	105-105-18	9 0 0 1 4 2 5 6
STREX system recessed	Jet Black	105-105-18	9 0 0 1 4 2 5 7
STREX system surface/suspended	Signal White	105-105-18	9 0 0 1 4 2 5 8
STREX system surface/suspended	Jet Black	105-105-18	9 0 0 1 4 2 5 9



WEVER & DUCRÉ
LIGHTING

STREX MODULE 1.0 OPAL

171385W5

DALI Selv Device

TYPE	L · W · H (MM)	ORDERCODE
STREX system	213·37·25	9 0 0 1 9 1 9 3



Power Supply 250W

TYPE	L · W · H (MM)	ORDERCODE
STREX system	400·40·22	9 0 2 1 8 9 0 3

Blank Cover 1m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Jet Black	1000·18·3	9 1 1 0 0 1 B 0
STREX system	Signal White	1000·18·3	9 1 1 0 0 1 W 0

Blank Cover 2m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Jet Black	2000·18·3	9 1 1 0 0 2 B 0
STREX system	Signal White	2000·18·3	9 1 1 0 0 2 W 0

Blank Cover 3m

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
STREX system	Jet Black	3000·18·3	9 1 1 0 0 3 B 0
STREX system	Signal White	3000·18·3	9 1 1 0 0 3 W 0

DIMMER

TYPE	L · W · H (MM)	ORDERCODE
DALI DIMMER FOR SWITCH	48·49·22	9 0 0 1 9 1 9 4