



WEVER & DUCRÉ
LIGHTING

MICK snooze 1.0

159654K3

GENERAL

Wall

Surface

Jet Black + Gold

IP20

Interior

185 lm

RAL 9005 ^a

LED

2700 K

CRI 90

L80 / 50000 h

3-step binning

OPTICAL

Beam angle 18°

PHYSICAL

Length 130 mm

Width 26 mm

Height 375 mm

0.39 kg

incl. switch on/off

Tilt min 90°

Tilt max 90°

Rotation 350°

ELECTRICAL

incl. power supply

220 - 240 V

Total connected power 7.5 W

LED Inset 5.6 W

PC3

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type


Notes

Quantity

Date



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

MICK snooze 1.0

159654K3

CONE DIAGRAM

18°

h (m)	E0° (lx)	ø (m)
1	1104	0.31
2	276	0.62
3	123	0.93
4	69	1.25
5	44	1.56

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.