



WEVER & DUCRÉ
LIGHTING

MAP 0.9

751264I4

Project
Type
Notes
Quantity
Date

GENERAL

Floor
 Recessed
 Inox
 IP67
 IK08
 Exterior
 475 lm

LED

3000 K
 CRI 80
 L70 / 50000 h
 3-step binning

OPTICAL

Flood
 Beam angle 44°

PHYSICAL



Diameter 85 mm
 Height 120 mm
 0.7 kg

ELECTRICAL


phase-cut dim
 220 - 240 V
 Total connected power 7.7 W
 PC2
 Safety distance 0.3 m

CUTOUT

Diameter 78 mm
 Recessed depth 135 mm



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

MAP 0.9

751264I4

CONE DIAGRAM

flood 44°

h (m)	EO ³ (lx)	ø (m)
1	736	0.81
2	184	1.62
3	82	2.43
4	46	3.24
5	29	4.05

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.94	0.88	0.83	0.77	0.72
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING

Recessed Housing

TYPE	Ø · H (MM)	ORDERCODE
MAP 0.9 CHART 0.9	ø132 · 125	9 0 0 1 2 2 0 2