



MOVE IN round

recessed


EN Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

DE Rundes Strahlerelement aus Aluminium in 2 Größen; pulverbeschichtet; werkzeuglose Montage im Montageset (randlos oder mit umlaufendem Rand) durch Kugelschnappsystem; spezielles Montagewerkzeug zur einfachen Installation des randlosen Gehäuses als Zubehör erhältlich; Strahlerelement werkzeuglos höhenverstellbar: deckenbündig, 25 mm oder 35 mm herausragend; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschattenbildung; energieeffiziente LEDs mit sehr guter Farbwiedergabe; hochwertiger, aluminiumbedampfter Reflektor mit Facettenoptik; präzise Abstrahlcharakteristik; gute Entblendung durch zurückversetzte Lichtpunktebene; optische Aufsätze als Zubehör

Quickinfo

2700 K, 3000 K
CRI ≥ 90, 3 SDCM
up to 1320 lm
L80 @ 50 000 h
non DIM, DALI-2

Types




Inset colours



Housing colours



Light distributions



tool-free height adjustment



trimless installation in plasterboard

Order options

COLOUR TEMPERATURE	
2700 K	4
3000 K	5

INSET COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● gold dust RAL 260-M	9

HOUSING COLOUR	
○ traffic white RAL 9016	7
● silver-grey	G
● jet black RAL 9005	8
● gold dust RAL 260-M	9


BEAM ANGLE	
MOVE IN 32/45	▲
spot 18°/14°	S
medium 23°/24°	M
flood 37°/39°	F

Options on request

MOUNTING HOUSING	
special colours	

CONVERTER EXTERNAL	
DIM 1-10V	

MOVE IN 32 round



SPOTLIGHT

incl. connection cable 600 mm

INSET POWER ¹	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
8.8 W 250 mA	2700 K	719 lm	0 6 3 - 8 1 1 1 :: 1 ▲
	3000 K	759 lm	

luminous flux CRI ≥ 90, medium 23°

MOVE IN 45 round



SPOTLIGHT

incl. connection cable 600 mm


INSET POWER ¹	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
13.5 W 400 mA	2700 K	1260 lm	0 6 3 - 8 1 2 1 :: 1 ▲
	3000 K	1320 lm	

luminous flux CRI ≥ 90, flood 36°

Mounting accessories

MOUNTING HOUSING TRIMLESS


for installation in plasterboard ceilings 9-25 mm



TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	63-93	0 6 3 - 8 8 1 1 1 1 7
MOVE IN 45	75-106	0 6 3 - 8 8 1 2 1 1 7


MOUNTING HOUSING WITH TRIM

for installation in ceilings from 2-25 mm



TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	65-93	0 6 3 - 8 8 2 1 1 1 1
MOVE IN 45	77-107	0 6 3 - 8 8 2 2 1 1 1

SPECIAL MOUNTING TOOL



TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	83-9	0 6 3 - 8 9 1 1 1 1 0
MOVE IN 45	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless

Electrical accessories

CONVERTER EXTERNAL supply 220-240 V AC, 50-60 Hz, □ PC II

TYPE	SPOTLIGHT	L-W-H (mm)	ORDER CODE
250 mA non DIM	MOVE IN 32	147-44-22	0 6 3 - 8 9 5 1 1 1 0
250 mA DALI-2	MOVE IN 32	147-44-22	0 6 3 - 8 9 5 1 1 3 0

400 mA non DIM	MOVE IN 45	143-43-30	0 6 3 - 8 9 5 3 1 1 0
400 mA DALI-2	MOVE IN 45	143-43-30	0 6 3 - 8 9 5 3 1 3 0

connection cable 1000 mm included

EXTENSION CABLE plug + socket

TYPE	L (mm)	ORDER CODE
extension cable	1000	0 4 9 - 4 9 5 1 1 0 0
extension cable	2000	0 4 9 - 4 9 5 1 2 0 0
extension cable	3000	0 4 9 - 4 9 5 1 3 0 0

max. extension cable length see mounting instructions

Optical accessories

HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	30-3	0 0 7 - 1 9 6 5 1 6 8
MOVE IN 45	42-3	0 0 7 - 1 9 6 5 1 8 8

¹ The power consumption of a light inset in watts is the entire current consumption excluding any necessary ballast.