



WEVER & DUCRÉ  
LIGHTING

# MILES 9.0

317278B3

|          |
|----------|
| Project  |
| Type     |
| Notes    |
| Quantity |
| Date     |

## GENERAL

Wall  
 Surface  
 Jet Black  
 IP20  
 Interior  
 1309 lm  
 RAL 9005<sup>a</sup>

## LED

2700 K  
 CRI 90  
 L80 / 50000 h  
 3-step binning



## PHYSICAL

Length 900 mm  
 Width 26 mm  
 Height 80 mm  
 2.13 kg


## ELECTRICAL

phase-cut dim  
 220 - 240 V  
 Total connected power 31 W  
 PC1  
 Safety distance 0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



## LIGHT DISTRIBUTION



[317278B3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.  
 © Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



**WEVER & DUCRÉ**  
LIGHTING

# MILES

## 9.0

317278B3

### Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF               | 0.96   | 0.92   | 0.88   | 0.84   | 0.81   |
| LSF                | 1      | 1      | 1      | 1      | 1      |

|                  |  |                   |                                 |
|------------------|--|-------------------|---------------------------------|
| MF               | $LMF \times RSMF \times LLMF \times LSF$ | RSMF <sup>a</sup> | Room Surface Maintenance Factor |
| MF               | Maintenance Factor                       | LLMF              | Lamp Lumens Maintenance Factor  |
| LMF <sup>a</sup> | Luminaire Maintenance Factor             | LSF               | Lamp Survival Faktor            |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.