

TRIUUM i IP67 SOLOVETRO

-  IP67
-  Class III 24Vdc
-  Class II 220-240Vac
-  Incasso a pavimento
Floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
-  Alimentazione integrata, collegare alla tensione di rete 220-240Vac
Built-in driver, connect directly to the line voltage to 220-240Vac
-  610 gr
-  Altamente riciclabile
Highly recyclable
-  IK 10




TRIUUM i IP67 SOLOVETRO

24Vdc

	7W 24Vdc	15W 24Vdc	Finiture Finish	Colore LED LED Colour	Filtri ottici Optical filters
Lumen Output 3000K	600lm	1000lm			
 10° Lens	734557._ _ _	734571._ _ _	 4 Nero - Black	 U 2200K	W Senza Filtro Without Filter
 25° Lens	7G4557._ _ _	7G4571._ _ _		 Y 2700K	D Frangiluce Louver
 40° Lens	744557._ _ _	744571._ _ _		 6 3000K	F Frangiluce Asy Asy Louver
 60° Lens	754557._ _ _	754571._ _ _		 W 3000K CRI > 90	
 Lente ellittica Elliptical lens	774557._ _ _	774571._ _ _		 J 3500K	
 Wall Washer	7W4557._ _ W			 9 4000K	

[1] 2200K
Disponibile solo per la
versione 7W
Available on the 7W
power version only




TRIUUM i IP67 SOLOVETRO

220-240Vac

	8W 220-240Vac	Finiture Finish	Colore LED LED Colour	Filtri ottici Optical filters
Lumen Output 3000K	600lm			
 10° Lens	734579._ _ _	 4 Nero - Black	 U 2200K	W Senza Filtro Without Filter
 25° Lens	7G4579._ _ _		 Y 2700K	D Frangiluce Louver
 40° Lens	744579._ _ _		 6 3000K	F Frangiluce Asy Asy Louver
 60° Lens	754579._ _ _		 W 3000K CRI > 90	
 Lente ellittica Elliptical lens	774579._ _ _		 J 3500K	
 Wall Washer	7W4579._ _ W		 9 4000K	

[1] 2200K
Disponibile solo per la
versione 7W
Available on the 7W
power version only



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

24Vdc CC20-F-24-N

ACCESSORI
ACCESSORIES



Controcassa in acciaio
Stainless Steel recessed box
TRIUUM i IP67 SOLOVETRO
24V
A01411.60



Controcassa in acciaio
Stainless Steel recessed box
TRIUUM i IP67 SOLOVETRO
220-240Vac
A01476.60



Accessorio per
estrazione
Removing tool
A01478.H0

EXAMPLE CODE COMPOSITION

123456.
OPTICAL FILTER
LED COLOUR
FINISH