



ROB
EXTERIOR
CEILING SURFACE



1.6

LED 8W | 220-240VAC | 50-60Hz
PCB 3-step | incl. power supply
aluminium powder coated
opal PMMA cover

0.80kg IP44 β -0.3°

3000K | >80 CRI | 600lm

CODE
701183W4
701183S4




2.6

LED 12W | 220-240VAC | 50-60Hz
COB 3-step | incl. power supply
aluminium powder coated
opal PMMA cover

1.30kg IP44 β -0.3°

3000K | >80 CRI | 1000lm

CODE
701283W4
701283S4



3.5

LED 20W | 220-240VAC | 50-60Hz
COB 3-step | incl. power supply
aluminium powder coated
opal PMMA cover

2.00kg IP44 β -0.3°

3000K | >80 CRI | 1600lm

CODE
701383W4
701383S4



ROB
CEILING SURFACE




1.6

LED 8W | 220-240VAC | 50-60Hz
PCB 3-step | incl. power supply
aluminium powder coated
opal PMMA cover

0.80kg IP44

3000K | >80 CRI | 600lm

CODE
701183W4
701183S4




2.6

LED 12W | 220-240VAC | 50-60Hz
PCB 3-step | incl. power supply
aluminium powder coated
opal PMMA cover

1.30kg IP44

3000K | >80 CRI | 1000lm

CODE
701283W4
701283S4



3.5

LED 20W | 220-240VAC | 50-60Hz
PCB 3-step | incl. power supply
aluminium powder coated
opal PMMA cover

2.00kg IP44

3000K | >80 CRI | 1600lm

CODE
701383W4
701383S4